



(10) **Patent No.:** US 9,409,275 B2
(45) **Date of Patent:** Aug. 9, 2016

- | | | | | |
|--------------|------|---------|-------------------|----------------------|
| 6,368,012 | B1 | 4/2002 | St. Onge et al. | |
| 6,873,880 | B2 | 3/2005 | Hooke et al. | |
| 7,631,560 | B2 * | 12/2009 | Lund et al. | 73/629 |
| 7,778,777 | B2 | 8/2010 | Chen | |
| 7,954,380 | B2 * | 6/2011 | Lund et al. | 73/629 |
| 8,374,835 | B2 * | 2/2013 | Lind et al. | 703/7 |
| 8,738,342 | B2 * | 5/2014 | Lind | E21B 41/00
703/10 |
| 2007/0289385 | A1 * | 12/2007 | Kiuchi | 73/627 |
| 2010/0282026 | A1 * | 11/2010 | Luce et al. | 76/108.1 |
| 2011/0209539 | A1 | 9/2011 | Breckstead et al. | |

OTHER PUBLICATIONS

Pushcorp, Inc.; "1000 Series Adjustable Force Device", product manual, dated Apr. 2001, 16 pages.

Pushcorp, Inc.; "1000 Series Adjustable Force Device", online product article, receive on Nov. 10, 2011, 4 pages.

(Continued)

Primary Examiner — Richard Chang
(74) Attorney, Agent, or Firm — Baker Botts L.L.P.

(57)

ABSTRACT

A method of removing unwanted material from an article having a variable form can include scanning the article and determining, based on the scanning, a location of the unwanted material, determining tool paths of a cutting tool which will result in removal of the unwanted material, and displacing the cutting tool along the tool paths, thereby removing the unwanted material. A material removal system for removing unwanted material from an oilfield drill bit can include a rotary indexing device which rotates the drill bit about a longitudinal axis of the drill bit, a scanning device which scans an outer surface of the drill bit, and a controller which determines a geometry of the drill bit, based on at least one scan by the scanning device, determines a location of the unwanted material, and determines tool paths of a cutting tool for removal of the unwanted material.

34 Claims, 9 Drawing Sheets

